Cutting, facing & orbital welding <3 mm wall thickness

V1.2 - 08/2017

SATF-40NDHX - 65NDHX $\mathbf{X} \mathbf{X} \mathbf{\Delta}$ INNOVATIVE ORBITAL SOLUTIONS - 115NDHX Viewing **Protection** window High protection against Fixed and transparent arcing outside the option electrode Power drive system with encoder Strengthening of Allows STARTING IN closing systems ALL ANGULAR Adjustable force POSITIONS closing systems. AXXAIR positions of the Allows precise electrode adjustment of the force of the jaws on the tube to be welded according to its Water cooled geometry Length of the cable: 5 metres Compatible with SAXX Fine tube welding welding generators Up to 2.5 mm (3 mm in some cases) Transport + suspension Remote control keypad These heads are delivered in their work site case and with a suspension assembly It incorporates an LED on the handle to indi-These heads can also cate whether the be used on the old machine is in welding AXXAIR welding stacycle or not. tions with adapter cables Join experience

45

Cutting, facing & orbital welding < 3 mm wall thickness

V1.2 - 08/2017

SATF 40NDHX - 65NDHX - 115NDHX

Technical characteristics:

Maximum welding current	120 A
100% Duty cycle	60 A

The new NDHX heads are used with SAXX range welding stations.

Changes have been incorporated in the upper part, for the closing and flap guide systems. The new adjustable force closing system allows you to precisely set the force of the jaws on the tube to be welded according to its geometry. Closing is more precise and the parts to be welded are better positioned.

The heads are cooled in two ways: on the electrode holder by contact and on the outer aluminium plates in the lower part.

This cooling is essential to guarantee a long service life of the parts because it minimizes distortion effects due to expansion.


- Cable extensions
- Remote electrodes
- Flange for welding elbows



Specific features

Option: Possibility of mounting a window in the upper part thus verifying the correct positioning of the electrode, for the parts to be welded, before starting the cycle.

CAUTION: If you use the head with a window, it is necessary to wear suitable eye protection (welding mask).



Product Code	Description	Tube welding machine for the following diameters (in mm):	Net weight	Customs code	Dimensions (AxBxC in mm)
SATF-40NDHX	Water-cooled closed head for SAXX	ø 6 to ø 40 mm	8.8 kg	85153 10000	336 x 122 x 40
SATF-65NDHX	Water-cooled closed head for SAXX	ø 6 to ø 65 mm	9.2 kg		366 x 152 x 40
SATF-115NDHX	Water-cooled closed head for SAXX	ø 25 to ø 115 mm	9.9 kg		421 x 222 x 40

